TECHNICAL FEATURES

MODEL:	**CR.RLV.CELLINI MATE**
SIZE:	**33,3x100**
THICKNESS(mm):	**8**
DATE:	**17/08/2022**
CODE:	**031.627.0803.10102**
GROUP:	**GROUP BIII UNE-EN 14411 Annex L / SASO ISO 13006:2018 Annex L**
TILE TYPE:	**GL**
FINISH:	**RECTIFIED MATT**
FAMILY:	**WHITE BODY WALL TILES**
NUMBER OF DESIGNS:	



TEST		RESULT
UNE-EN ISO 10545-2	DIMENSIONAL FEATURES	**COMPLIES WITH THE STANDARD**
UNE-EN ISO 10545-3	WATER ABSORPTION	**16%**
UNE-EN ISO 10545-4	MODULUS OF RUPTURE	**>400 N**
	BREAKING STRENGTH	**15-25 N/mm2**
UNE-EN ISO 10545-8	LINEAR THERMAL EXPANSION	**<7,0 x 10-6 ºC-1**
UNE-EN ISO 10545-9	THERMAL SHOCK RESISTANCE	**RESISTS**
UNE-EN ISO 10545-11	CRAZING RESISTANCE	**RESISTS**
UNE-EN ISO 10545-13	CHEMICAL RESISTANCE - AMMONIUM CHLORIDE 100 G/L	**A**
	CHEMICAL RESISTANCE - SODIUM HYPOCHLORITE 20 MG/L	**A**
	CHEMICAL RESISTANCE - HYDROCHLORIC ACID 3%	**COMPLIES WITH THE STANDARD**
	CHEMICAL RESISTANCE - CITRIC ACID 100 G/L	**COMPLIES WITH THE STANDARD**
	CHEMICAL RESISTANCE - POTASSIUM HYDROXYDE 30 G/L	**COMPLIES WITH THE STANDARD**
UNE-EN ISO 10545-14	STAIN RESISTANCE - GREEN AGENT IN LIGHT OIL	**5**
	STAIN RESISTANCE - IODINE SOLUTION IN ALCOHOL	**5**
	STAIN RESISTANCE - OLIVE OIL	**5**

Declaration of Performance:

https://www.pamesa.com/ERP/4.0/empresas/151/045/ficheros/t00030006/111/DdP_DoP_N001CPR2013.pdf

TECHNICAL DEPARTMENT
PAMESA CERÁMICA