ITALGRANITI
SUPERIOR ITALIAN SURFACES

ICÔNE BLEU

SPECIFICATION

PORCELAIN STONEWARE

MATERIAL

Porcelain stoneware.
Classified in GROUP BIa UGL CON Ev ≤ 0,5%.
Complies with all the requirements of UNI EN 14411 ISO 13006 APP. G standards.

COLOR			SIZES	SURFACE	THICKNESS
	BLANC	V2	**MATTE RECTIFIED** 120x120 (48″x48″) . 60x120 (23⅝″x48″) . 80x80 (32″x32″) . 60x60 (23⅝″x23⅝″) . 30x60 (11⅞″x23⅝″) . 20x60 (8″x23⅝″) . 10x60 (4″x23⅝″) **BRUSHED RECTIFIED** 80x80 (32″x32″) **LIGNE RECTIFIED** 20x120 (8″x48″) **ANTISLIP RECTIFIED** 60x120 (23⅝″x48″) **OPEN ANTISLIP RECTIFIED (20 MM)*** 80x80 (32″x32″) (*Only BEIGE, GRIS)	**MATTE** **BRUSHED** **LIGNE** **ANTISLIP** **OPEN ANTISLIP (20MM)**	**9 MM** **20 MM**
	BEIGE	V2			
	TAUPE	V2			
	GRIS	V2			
	NOIR	V2			

PROCESS certified according to the ISO 9001 quality standard

Product obtained from exceptionally pure, choice quality raw materials, including light-coloured clays, feldspar fluxes, kaolins, sands and coloured ceramic pigments. Pressing in hydraulic presses allows a pressure of over 500kg/cm2 to be applied to the product, guaranteeing dimensional precision, planarity and high mechanical strength.
The product's colours and patterns are achieved with the innovative Digital Technology.
The materials are fired in single-layer roller kilns at temperatures of over 1,220°C.

GREEN BUILDING: CERTIFIED ENVIRONMENTAL SUSTAINABILITY

The tiles in the Icône Bleu collection are ideal for eco-sustainable building:

- They are produced in plants which have an EMAS-ISO 14001 certified environmental management system.
- They help to obtain credits for the construction of buildings in accordance with the LEED certification programme.

Size .....

Finishes .....

Color ..... Type .....

放射性水平A类 LEED COMPLIANT EMAS GESTIONE AMBIENTALE VERIFICATA N. Registro IT-000058 ISO 14001 BUREAU VERITAS Certification ISO 45001 BUREAU VERITAS Certification ISO 9001 BUREAU VERITAS Certification

ITALGRANITI
SUPERIOR ITALIAN SURFACES

ICÔNE BLEU

FLOOR | WALL | FACING SYSTEMS | RESIDENTIAL INDOOR | RESIDENTIAL OUTDOOR | PUBLIC INDOOR | PUBLIC OUTDOOR | HEAVY TRAFFIC

TECHNICAL TABLE PORCELAIN STONEWARE

CONFORMING TO STANDARDS
EN 14411 ISO 13006 ANNEX G GROUP BIa UGL CON Ev ≤ 0,5%

PHYSICAL PROPERTIES	TESTING METHOD	REFERENCE STANDARD				PRODUCT VALUES
			7cm ≤ N < 15 cm (mm)	N ≥ 15 cm (%) (mm)		Rectified
Sizes	EN ISO 10545-2	Length and width	±0.9	±0.6	±2.0	±0.2 %
		Thickness	±0.5	±5.0	±0.5	±5 %
		Linearity	±0.75	±0.5	±1.5	±0.2 %
		Wedging	±0.75	±0.5	±2.0	±0.2 %
		Warpage	±0.75	±0.5	±2.0	±0.2 %
		Appearance: percentage of acceptable tiles, per lot	95 % min.	95 % min.	-	
Water absorption %	EN ISO 10545-3	Ev ≤ 0,5%				< 0,1%
Modulus of rupture	EN ISO 10545-4	Valore medio 35 N/mm² min.				45 N/mm²
Breakage resistence		sp. > = 7,5 mm: min 1300 N sp. < 7,5 mm: min 700 N				2500 N (9 mm)
Scratch resistance	EN ISO 10545-6	175 mm3 max.				Average < 150 mm3
Thermal expansion coefficient	EN ISO 10545-8	Declared value				6,8 MK^{-1}
Thermal shock resistance	EN ISO 10545-9	Pass according to iso 10545-1				* Resistant
Frost resistance	EN ISO 10545-12	Pass according to iso 10545-1				* Resistant
Resistance to low concentrations of acids and alkali	EN ISO 10545-13	Declared value				* Resistant
Resistance to high concentrations of acids and alkali		Declared value				* Resistant
Resistance to domestic chemicals and additi-ves for swimming pools		UB min.				UA
Stain resistance of unglazed matte porcelain	EN ISO 10545-14	Declared value				* Resistant
Friction coefficient (slipperiness)	DIN 51130	If needed				Declared value
	DIN 51097					Declared value
	B.C.R.A. - D.M.236/ 89					> 0,40 Dry / > 0,40 Wet
	ANSI A326.3					≥ 0,42 Wet

Assessed by Ongreening, this product can potentially contribute to major green rating systems.
For more info visit Ongreening.com
LEED BREEAM HK Beam Plus CAM HQM WELL GREEN STAR

Technical details available on:
www.italgranitigroup.com